


CHARACTER TYPE LCM



Display Format Char x line	Model No.	Outline Dimension (WxH)mm	Effective Viewing Area (WxH)mm	Dot Size (WxH)mm	Dot Pitch (WxH)mm	Driving Method (Duty)	Interface
8x2	WH0802A1	58.0x32.0	38.0x16.0	2.96x5.56	0.56x0.66	1/16	6800
	WH0802A2	58.0x32.0	38.0x16.0	2.96x5.56	0.56x0.66	1/16	SPI
	WH0802A5	58.0x32.0	38.0x16.0	2.96x5.56	0.56x0.66	1/16	I2C
12x2	WH1202A	55.7x32.0	46.0x14.5	2.65x5.50	0.45x0.60	1/16	6800
16x1	WH1601A	80.0x36.0	66.0x16.0	3.07x6.56	0.55x0.75	1/16	6800
	WH1601B	85.0x28.0	66.0x16.0	3.07x6.56	0.55x0.75	1/16	6800
	WH1601L	122.0x33.0	99.0x13.0	4.84x8.06	0.92x1.10	1/16	6800
16x2	WH1602A	84.0x44.0	66.0x16.0	2.95x5.55	0.55x0.65	1/16	6800
	WH1602A2	84.0x44.0	66.0x16.0	2.95x5.55	0.55x0.65	1/16	SPI
	WH1602B	80.0x36.0	66.0x16.0	2.95x5.55	0.55x0.65	1/16	6800
	WH1602B1	80.0x36.0	66.0x16.0	2.95x5.55	0.55x0.65	1/16	SPI
	WH1602B3	80.0x36.0	66.0x16.0	2.95x5.55	0.55x0.65	1/16	I2C
	WH1602C	85.0x36.0	66.0x16.0	2.95x5.55	0.55x0.65	1/16	6800
	WH1602C1	85.0x36.0	66.0x16.0	2.95x5.55	0.55x0.65	1/16	SPI
	WH1602C2	85.0x36.0	66.0x16.0	2.95x5.55	0.55x0.65	1/16	I2C
	WH1602D	85.0x30.0	66.0x16.0	2.95x5.55	0.55x0.65	1/16	6800
	WH1602D1	85.0x30.0	66.0x16.0	2.95x5.55	0.55x0.65	1/16	SPI
	WH1602J	80.0x36.0	66.0x16.0	2.95x5.55	0.55x0.65	1/16	6800
	WH1602L1	122.0x44.0	99.0x24.0	4.84x9.66	0.92x1.10	1/16	6800
	WH1602M	85.0x32.6	66.0x16.0	2.95x5.55	0.55x0.65	1/16	6800
	WH1602O	85.0x25.2	66.0x16.0	2.95x5.55	0.55x0.65	1/16	6800
	WH1602P	85.0x25.2	66.0x16.0	2.95x5.55	0.55x0.65	1/16	6800
	WH1602S	59.0x29.3	52.0x15.3	2.45x4.67	0.45x0.54	1/16	6800
	WH1602S1	59.0x29.3	52.0x15.3	2.45x4.67	0.45x0.54	1/16	SPI
	WH1602T	65.4x28.2	54.8x19.0	3.05x5.57	0.51x0.67	1/16	6800
	WH1602V1	66.7x23.3	61.0x15.9	2.95x5.55	0.55x0.65	1/16	6800
	WH1602W	80.0x36.0	66.0x16.0	2.95x5.55	0.55x0.65	1/16	6800
16x4	WH1604A	87.0x60.0	62.0x26.0	2.95x4.75	0.55x0.55	1/16	6800
	WH1604B	70.6x60.0	60.0x32.6	2.95x4.75	0.55x0.55	1/16	6800
20x2	WH2002A	116.0x37.0	85.0x18.6	3.2x5.55	0.60x0.65	1/16	6800
	WH2002A2	116.0x37.0	85.0x18.6	3.2x5.55	0.60x0.65	1/16	SPI
	WH2002A2	116.0x37.0	85.0x18.6	3.2x5.55	0.60x0.65	1/16	I2C
	WH2002B	116.0x37.0	85.0x18.6	3.2x5.55	0.60x0.65	1/16	6800
	WH2002B1	116.0x37.0	85.0x18.6	3.2x5.55	0.60x0.65	1/16	SPI
	WH2002B2	116.0x37.0	85.0x18.6	3.2x5.55	0.60x0.65	1/16	I2C
	WH2002D	89.0x21.5	75.0x15.0	2.95x5.15	0.55x0.60	1/16	6800
	WH2002L	180.0x40.0	149.0x23.0	6.0x9.66	1.12x1.12	1/16	6800
	WH2002M	146.0x43.0	123.0x23.0	4.84x9.22	0.92x1.10	1/16	6800
WH2002G	115.0x36.0	85.0x18.6	3.20x5.55	0.60x0.65	1/16	6800	
20x4	WH2004A	98.0x60.0	77.0x25.2	2.95x4.75	0.55x0.55	1/16	6800
	WH2004A1	98.0x60.0	77.0x25.2	2.95x4.75	0.55x0.55	1/16	SPI
	WH2004A2	98.0x60.0	77.0x25.2	2.95x4.75	0.55x0.55	1/16	I2C
	WH2004B	98.0x60.0	77.0x25.2	2.95x4.75	0.55x0.55	1/16	6800
	WH2004D	77.0x47.0	60.0x22.0	2.30x4.03	0.42x0.46	1/16	6800
	WH2004D1	77.0x47.0	60.0x22.0	2.30x4.03	0.42x0.46	1/16	SPI
	WH2004D2	77.0x47.0	60.0x22.0	2.30x4.03	0.42x0.46	1/16	I2C
	WH2004L	146.0x62.5	123.5x43.0	4.84x9.22	0.92x1.10	1/16	6800
	WH2004L1	146.0x62.5	123.5x43.0	4.84x9.22	0.92x1.10	1/16	SPI
	WH2004L2	146.0x62.5	123.5x43.0	4.84x9.22	0.92x1.10	1/16	I2C
	WH2004H	87.0x58.0	74.4x24.8	2.95x4.75	0.55x0.55	1/16	6800
	WH2004H1	87.0x58.0	74.4x24.8	2.95x4.75	0.55x0.55	1/16	SPI
	WH2004H2	87.0x58.0	74.4x24.8	2.95x4.75	0.55x0.55	1/16	I2C
	WH2004G	87x58.0	74.4x24.8	2.95x4.75	0.55x0.55	1/16	6800
	WH2004G1	87x58.0	74.4x24.8	2.95x4.75	0.55x0.55	1/16	SPI
	WH2004G2	87x58.0	74.4x24.8	2.95x4.75	0.55x0.55	1/16	I2C
24x2	WH2402A	118.0x36.0	94.5x16.0	3.2x5.55	0.60x0.65	1/16	6800
40x2	WH4002A	182.0x33.5	154.4x16.5	3.2x5.55	0.60x0.65	1/16	6800
40x4	WH4004A	190.0x54.0	147.0x29.5	2.78x4.89	0.50x0.55	1/16	6800

